



TECHNICAL INFORMATION

032-200 TOLUIDINE RED 3 MEDIUM

C. I. PIGMENT RED 3 C. I. NO. 12120

DESCRIPTION

A bright medium shade red with good lightfastness in the full shade, but has a tendency to bleed in solvent.

TYPICAL PHYSICAL PROPERTIES

Bulk Density	11.9 lbs/gal
pH (10% Aqueous Slurry)	6.0 - 7.0
Moisture Content %	< 2.0
Sl. Soluble	
Water Soluble Salts %	< 2.0
Soluble	
Oil Absorption	53 wt/100 wt

BLEED CHARACTERISTICS

Xylene	Soluble
Ethanol	Soluble
Mineral Spirit	
Lacquer Solvents	
Water	Trace

LIGHTFASTNESS

Full Shade:	Good
Tint:	Poor

CHEMICAL RESISTANCE

Acid:	Excellent
Alkali:	Very Good

HEAT STABILITY (Coatings)

230° F 110° C

SUGGESTED USES

032-200 is used in trade sales paint, maintenance coatings and selected industrial coatings in or near the full shade. This pigment is not recommended in plastics.

LANSCO COLORS

305 WEST GRAND AVE., MONTVALE, NJ 07645 • 201-307-5995 • FAX 201-307-5855

The information contained herein is true and accurate to the best of our knowledge, but is provided without warranty or guarantee. Since the conditions of use are beyond our control, Landers-Segal Color Co., Inc. assumes no legal responsibility for use or reliance upon the information contained herein. Landers-Segal Color Co. strongly recommends careful screening/testing before using its products in production.