



1144 Disazo Red 144

Description: 1144 is a medium to slightly blue shade, red pigment with high purity, tinting strength and excellent heat stability primarily used in the coloration of plastics.

| | | | |
|----------------------|-----------------|-------------------------|-----------|
| Chemical Type | Disazo Red | Constitution No. | 20735 |
| Color Index | Pigment Red 144 | CAS No. | 5280-78-4 |

Resistance Properties

| | | | |
|------------------------|---|----------------------|-------|
| MEK | 4 | Ethanol | 4 - 5 |
| Water | 5 | Ethyl Acetate | 5 |
| Mineral Spirits | 5 | Acid | 5 |
| Xylene | 4 | Alkali | 5 |

Legend: 1=Poor, 2=Fair, 3=Good, 4=Very Good, 5=Excellent

Product Characteristics

| | | | |
|--|--------------|---|-------|
| Migration (1-5) | 5 | Lightfastness (1-8): Masstone | 7 - 8 |
| Heat Stability (°C/°F) | 299°C (HDPE) | Lightfastness (1-8): Tint 1:10 | 7 - 8 |
| Warpage Rating (1-3) * Plastic Only | | Weatherfastness (1-5): Masstone | |
| Overpaint Resistance * Paints Only | | Weatherfastness (1-5): Tint 1:10 | |

Warpage: 1 = minimal, 2 = some, 3 = severe Weatherfastness: 1=Poor, 2=Fair, 3=Good, 4=Very Good, 5=Excellent Lightfastness: 1-2=Poor, 3-4=Fair, 5=Good, 6-7=Very Good, 8=Excellent

Physical Properties

| | | | |
|--|--------|----------------------------|-----------|
| Particle Size (µm) | | pH | 5.5 - 7.5 |
| Specific Surface Area (m²/g) | | Specific Gravity | 1.5 |
| Oil Absorption (g/100g) | | Bulk Density (kg/L) | |
| Moisture Content (%) | ≤ 1.0% | Bulk Volume (L/kg) | |

Applications

| Plastics | | Coatings | | Inks | | Other | |
|----------|-------------------------------------|----------------------|-------------------------------------|---------------|--------------------------|---------------|---|
| PVC | ■ | Decorative | <input type="checkbox"/> | Water Flexo | <input type="checkbox"/> | Paper | |
| PE | ■ | Automotive/Aerospace | <input type="checkbox"/> | Solvent Flexo | ■ | Rubber | ■ |
| PP | ■ | Industrial | <input checked="" type="checkbox"/> | InkJet | <input type="checkbox"/> | Finger Paints | |
| PS | ■ | Powder | <input checked="" type="checkbox"/> | UV | <input type="checkbox"/> | Seed Coatings | |
| PET | <input checked="" type="checkbox"/> | | | Offset | <input type="checkbox"/> | | |
| Fiber | ■ | | | | | | |

Not Frequently Used Limited Recommended

Comments:

DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY DCL: The information contained herein is true and accurate to the best of our knowledge and are deemed as typical values, being therefore provided without warranty or guarantee. Since the conditions of use are beyond our control, DCL disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein. DCL strongly recommends careful screening/testing before using its products in production.