



1274-D Hansa Yellow 74

Description: 1274-D is a medium shade Hansa Yellow with good lightfastness and opacity.

| | | | |
|----------------------|-------------------|-------------------------|-----------|
| Chemical Type | Hansa Yellow | Constitution No. | 11741 |
| Color Index | Pigment Yellow 74 | CAS No. | 6358-31-1 |

Resistance Properties

| | | | |
|------------------------|-------|----------------------|-------|
| MEK | 3 | Ethanol | 3 - 4 |
| Water | 5 | Ethyl Acetate | 3 - 4 |
| Mineral Spirits | 4 | Acid | 5 |
| Xylene | 2 - 3 | Alkali | 5 |

Legend: 1=Poor, 2=Fair, 3=Good, 4=Very good, 5=Excellent

Product Characteristics

| | | | |
|--|---------------|---|---|
| Migration (1-5) | | Lightfastness (1-8): Masstone | 8 |
| Heat Stability (°C/°F) | 140°C (Paint) | Lightfastness (1-8): Tint 1:10 | 7 |
| Warpage Rating (1-3) * Plastic Only | | Weatherfastness (1-5): Masstone | |
| Overpaint Resistance * Paints Only | | Weatherfastness (1-5): Tint 1:10 | |

Warpage: 1 = minimal, 2 = some, 3 = severe Weatherfastness: 1=Poor, 2=Fair, 3=Good, 4=Very Good, 5=Excellent Lightfastness: 1-2=Poor, 3-4=Fair, 5=Good, 6-7=Very Good, 8=Excellent

Physical Properties

| | | | |
|--|------|----------------------------|-----------|
| Particle Size (µm) | | pH | 5.5 - 7.5 |
| Specific Surface Area (m²/g) | | Specific Gravity | 1.48 |
| Oil Absorption (g/100g) | 43 | Bulk Density (kg/L) | |
| Moisture Content (%) | <1.5 | Bulk Volume (L/kg) | |

Applications

| Plastics | Coatings | Inks | Other |
|---------------------------------------|---|--|----------------------|
| PVC <input type="checkbox"/> | Decorative <input checked="" type="checkbox"/> | Water Flexo <input checked="" type="checkbox"/> | Paper |
| PE <input type="checkbox"/> | Automotive/Aerospace <input type="checkbox"/> | Solvent Flexo <input checked="" type="checkbox"/> | Rubber |
| PP <input type="checkbox"/> | Industrial <input checked="" type="checkbox"/> | InkJet <input type="checkbox"/> | Finger Paints |
| PS <input type="checkbox"/> | Powder <input type="checkbox"/> | UV <input checked="" type="checkbox"/> | Seed Coatings |
| PET <input type="checkbox"/> | | Offset <input type="checkbox"/> | |
| Fiber <input type="checkbox"/> | | | |

Not Frequently Used Limited Recommended

Comments: May exhibit blooming, not recommended for baking systems.

DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY DCL: The information contained herein is true and accurate to the best of our knowledge and are deemed as typical values, being therefore provided without warranty or guarantee. Since the conditions of use are beyond our control, DCL disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein. DCL strongly recommends careful screening/testing before using its products in production.