

## **GemSperse Yellow BA1**

**Description:** Surfactant and Water Based Dispersion of Yellow 1

Chemical Type	9	Monoazo	o Yellow		Constitution No.		11680		
Color Index		Pigment	Yellow 1		CAS No.	CAS No.		2512-29-0	
Resistance Properties									
MEK		3			Ethanol	•		4	
Water		4			Ethyl Acetate		3		
Mineral Spirits	;	4			Acid		5		
Xylene	-d 4 1/	2-3			Alkali		5		
Legend: 1=Poor, 2=Fair, 3=Good, 4=Very Good, 5=Excellent  Product Characteristics									
Heat Stability (°C/°F)  140°C Weatherfastness (1-5): Masstone									
Lightfastness	Masstone	6		Weatherfastness (1-5): Tint 1:10					
<b>Lightfastness</b> Weatherfastness: 1=Poor, 2=F		5 Lightfastness	s: 1-2=Poo	1-2=Poor, 3-4=Fair, 5=Good, 6-7=VG, 8=Excellent					
Physical Properties									
Fineness of Grind (μm)			<10		Specific Gravity		1 - 1.3		
Volatile Organic Content (ppm)			<700		Viscosity (cP)		1000 - 3000	1000 - 3000	
рН			8 - 9.5		Pigment Content (%)		43		
Applications									
Plastics	• •				Inks Other				
PVC		Decorative			Water Flexo		Paper		
PE		Automotive/Aerospace			Solvent Flexo		Rubber Latex		
PP		Industrial			InkJet		Finger Paints		
PS		Powder			UV		Seed Coatings		
PET					Offset				
☐ Not Frequently Used ☐ Limited ☐ Recommended									

**Comments:** A mid-shade yellow with moderate color strength. Good fastness to light and chemicals, but only moderate solvent fastness. Poor heat stability.

**DISCLAIMER OF LIABILITY FOR RELIANCE ON INFORMATION PROVIDED BY DCL:** The information contained herein is true and accurate to the best of our knowledge and are deemed as typical values, being therefore provided without warranty or guarantee. Since the conditions of use are beyond our control, DCL disclaims all liability and assumes no legal responsibility for damages resulting from use of or reliance upon the information contained herein. DCL strongly recommends careful screening/testing before using its products in production. Shelf life for GemSperse products is 1 year.